

# Durable Locks for Every Need

PointCentral, in close collaboration with our strategic partner Yale, is proud to provide our property managers with high quality durable locks for both residential and commercial applications.

## How to choose the right lock? \_\_\_\_\_

The American National Standards Institute (ANSI) and Builders Hardware Manufacturers Association (BHMA) have developed durability, strength and performance standards for every type of door hardware on the market. To receive ANSI/BHMA grade certification, the products must undergo a series of rigorous operational and security tests to comply with the standards.

### ANSI GRADE 1

This is the highest level of ANSI grade. This is a heavy-duty commercial security lock that is specifically designed for high traffic and superior security. As the strongest grade, it is predominantly found in commercial and industrial applications, although it is also suggested for residential applications, especially for doors with high usage.

### ANSI GRADE 2

These locks are not expected to be as heavy-duty as Grade 1, but do meet light commercial requirements. Grade 2 locks exceed most apartment building, rental property and residential requirements.

### ANSI GRADE 3

This is a basic residential security lock that meets the lowest acceptable quality standards for locks by the ANSI. PointCentral does not offer Grade 3 locks.

**Please refer to the attached PointCentral Lock Option comparison chart for the ANSI Grade of the different lock models PointCentral offers.**

### MARINE GRADE LOCKS

The Yale Push Button Deadbolt (YRD216) lock is Marine Grade, making it better able to withstand the moisture and temperature of harsher environments.

Marine Grade enhancements include:

- All connector contacts are gold plated.
- Double layer conformal coating applied to circuit board.
- Gasket plug prevents moisture from traveling to the interior of the lock.
- Custom gasket on interior lock routes moisture away from electronic components.

**Marine Grade locks are recommended for marine environments and any area that experiences high levels of humidity.**



**NTB610/620  
GRADE 1**



**YRD216 MG  
GRADE 2**

# PointCentral Lock Options

PointCentral, in close collaboration with our strategic partner Yale, is proud to provide property managers with high quality and durable locks for both residential and commercial applications.



	Deadbolt 500 Series YRD216/226	Deadbolt Keyfree YRD156	Lever NexTouch NTB610/620
Keypad Access	Push Button (YRD216) MG Touchscreen (YRD226)	Touchscreen	Push Button (NTB610) Touchscreen (NTB620)
ANSI Grade	Grade 2 Certified	Grade 2 Certified	Grade 1 Certified
Door Thickness	1-3/8" to 2-1/4" 1-3/4" to 1-3/4" (Gasket Required)	1-3/8" to 2-1/4"	1-3/8" to 1-3/4"
Motorized Lock/Unlock	✓	✓	✓
9V Battery Backup	✗	✓	✗
Mechanical Key Backup	✓	✗	✓
Finishes	Satin Nickel Oil Rubbed Bronze	Satin Nickel Oil Rubbed Bronze	Satin Nickel
Environmental Operating Conditions	-22°F to 140°F	-22°F to 140°F	-40°F to 140°F
Weather Resistant	✓	✓	✓
ADA Compliance	✗	✗	✓
Lock Body Type	Motorized Deadbolt	Motorized Deadbolt	Commercial Cylindrical Lock
Features	Enhanced security of the deadbolt. Fits standard 2-1/4" deadbolt bore.	Security of the deadbolt. Fits standard 2-1/4" deadbolt bore.	Heavy-duty and durable. One piece of hardware for lock and access.
Considerations	Requires separate lever/knob. Deadbolt should always be retracted when door closes to avoid damage to door frame and the deadbolt latch.	Requires separate lever/knob. Deadbolt should always be retracted when door closes to avoid damage to door frame and the deadbolt latch.	Latch guard recommended for extra security to prevent tampering with the latch.
Recommended Usage	General use on any standard door.	General use on any standard door. Not recommended for high humidity areas or environments where the lock will be exposed to direct sun.	Recommended for self-closing doors and high usage doors.

Learn more at [www.pointcentral.com](http://www.pointcentral.com) | 888-532-3032 | [info@pointcentral.com](mailto:info@pointcentral.com)

# PointCentral Lock Options

PointCentral, in close collaboration with our strategic partner Yale, is proud to provide property managers with high quality and durable locks for both residential and commercial applications.



	Lever Keyfree YRL236/256	Deadbolt Interconnected YRC216	Deadbolt Interconnected YRC226
Keypad Access	Push Button (YRL236) Touchscreen (YRL256)	Push Button	Touchscreen
ANSI Grade	Grade 2 Certified	Grade 2 Certified	Grade 2 Certified
Door Thickness	1-3/8" to 1-3/4"	1-3/8" to 1-3/4"	1-3/8" to 1-3/4"
Motorized Lock/Unlock	✓	✓	✓
9V Battery Backup	✓	✗	✗
Mechanical Key Backup	✗	✓	✓
Finishes	Satin Nickel	Satin Nickel	Satin Nickel
Environmental Operating Conditions	-22°F to 140°F	-22°F to 140°F	-22°F to 140°F
Weather Resistant	✓	✓	✓
ADA Compliance	✓	✓	✓
Lock Body Type	Commercial Cylindrical Lock	Motorized Deadbolt	Motorized Deadbolt
Features	One piece of hardware for lock and access.	From the inside, both the latchbolt and the deadbolt are retracted in a single motion. Meets most multi-family building requirements.	From the inside, both the latchbolt and the deadbolt are retracted in a single motion. Meets most multi-family building requirements.
Considerations	Latch guard recommended for extra security to prevent tampering with the latch.	Requires bore hold distance of 4" or 5-1/2" center-to-center.	Requires bore hold distance of 4" or 5-1/2" center-to-center.
Recommended Usage	Self-closing doors and non-primary access doors such as the entrance to the garage.	Multi-family buildings that require interconnected style lock.	Multi-family buildings that require interconnected style lock.

Learn more at [www.pointcentral.com](http://www.pointcentral.com) | 888-532-3032 | [info@pointcentral.com](mailto:info@pointcentral.com)

# PointCentral Lock Options

PointCentral, in close collaboration with our strategic partner Yale, is proud to provide property managers with high quality and durable locks for both residential and commercial applications.



	Deadbolt Keyfree YRC246	Sectional Mortise NTM610	Sectional Mortise NTM615
Keypad Access	Touchscreen	Push Button	Push Button
ANSI Grade	Grade 2 Certified	Grade 1 Certified	Grade 1 Certified
Door Thickness	1-3/8" to 1-3/4"	1-3/4" to 2-1/4"	1-3/4" to 2-1/4"
Motorized Lock/Unlock	✓	✓	✓
9V Battery Backup	✓	✓	✓
Mechanical Key Backup	✗	✓	✓
Finishes	Satin Nickel	Brass, Bronze, Satin Nickel, Black Suede	Brass, Bronze, Satin Nickel, Black Suede
Environmental Operating Conditions	-22°F to 140°F	-40°F to 140°F	-40°F to 140°F
Weather Resistant	✓	✓	✓
ADA Compliance	✓	✓	✓
Lock Body Type	Motorized Deadbolt	Motorized Deadbolt	Motorized Deadbolt
Features	From the inside, both the latchbolt and the deadbolt are retracted in a single motion. Meets most multi-family building requirements.	Key override. Mortise style door compatible.	Key override with deadbolt. Mortise style door compatible.
Considerations	Requires bore hold distance of 4" or 5-1/2" center-to-center.	No deadbolt. Requires mortise style door or modification.	Requires mortise style door or modification.
Recommended Usage	Multi-family buildings that require interconnected style lock.	Mortise lock replacement.	Mortise lock replacement.

Learn more at [www.pointcentral.com](http://www.pointcentral.com) | 888-532-3032 | [info@pointcentral.com](mailto:info@pointcentral.com)

# PointCentral Lock Options

PointCentral, in close collaboration with our strategic partner Yale, is proud to provide property managers with high quality and durable locks for both residential and commercial applications.



	Sectional Mortise NTM620	Sectional Mortise NTM625	Sectional Mortise NTM645
Keypad Access	Touchscreen	Touchscreen	Touchscreen
ANSI Grade	Grade 2 Certified	Grade 1 Certified	Grade 1 Certified
Door Thickness	1-3/4" to 2-1/4"	1-3/4" to 2-1/4"	1-3/4" to 2-1/4"
Motorized Lock/Unlock	✓	✓	✓
9V Battery Backup	✓	✓	✓
Mechanical Key Backup	✓	✓	✗
Finishes	Brass, Bronze, Satin Nickel, Black Suede	Brass, Bronze, Satin Nickel, Black Suede	Brass, Bronze, Satin Nickel, Black Suede
Environmental Operating Conditions	-40°F to 140°F	-40°F to 140°F	-40°F to 140°F
Weather Resistant	✓	✓	✓
ADA Compliance	✓	✓	✓
Lock Body Type	Motorized Deadbolt	Motorized Deadbolt	Motorized Deadbolt
Features	Key override. Mortise style door compatible.	Key override with deadbolt. Mortise style door compatible.	Mortise style door compatible.
Considerations	No deadbolt. Requires mortise style door or modification.	Requires mortise style door or modification.	No key override with deadbolt. Requires mortise style door or modification.
Recommended Usage	Mortise lock replacement.	Mortise lock replacement.	Mortise lock replacement.

Learn more at [www.pointcentral.com](http://www.pointcentral.com) | 888-532-3032 | [info@pointcentral.com](mailto:info@pointcentral.com)

# PointCentral Lock Options

PointCentral, in close collaboration with our strategic partner Yale, is proud to provide property managers with high quality and durable locks for both residential and commercial applications.



## Assure Lock for Andersen Patio & Entry Doors YRM276

Keypad Access	Touchscreen
ANSI Grade	N/A
Door Thickness	Fits A & E Series Andersen Doors
Motorized Lock/Unlock	✓
9V Battery Backup	✓
Mechanical Key Backup	✗
Finishes	Satin Nickel, Black, White
Environmental Operating Conditions	-22°F to 140°F
Weather Resistant	✓
ADA Compliance	✓
Lock Body Type	Mortise
Features	No key means no lost keys and no pick and bump break-ins. Touchscreen, Bluetooth & Wi-Fi or Z-Wave Plus connectivity. Monitor, lock and unlock from anywhere with Wi-Fi and Bluetooth.
Considerations	Only fits Andersen A & E series doors.
Recommended Usage	Hinged patio and entry doors.

Learn more at [www.pointcentral.com](http://www.pointcentral.com) | 888-532-3032 | [info@pointcentral.com](mailto:info@pointcentral.com)